

Diesel Generator Powered by Mitsubishi | Three Phase Specifications:(750KVA-2250KVA)

50HZ

Genset Model	ESP		PRP		Fuel Cons L/H(75%)	Open L*W*H(mm)	Silent L*W*H(mm)	Engine Model	Country of origin	Cyl Arrangement	Displacement (L)	Gov	Cooling
	KVA	KW	KVA	KW									
KGM750	800	640	750	600	120	4080*1715*1985	ISO 20ft Contaienr	S6R2-PTAA	●	6L	29.96	E	Water
KGM800	880	704	800	640	130.6	4080*1715*1985	ISO 20ft Contaienr	S12A2-PTA	●	12V	33.93	E	Water
KGM1000	1100	880	1000	800	165	4400*1756*2440	ISO 20ft Contaienr	S12H-PTA	●	12V	37.11	E	Water
KGM1250	1400	1120	1250	1000	208	4400*1756*2440	ISO 40ft Contaienr	S12R-PTA	●	12V	49.03	E	Water
KGM1400	1540	1232	1400	1120	218	4515*2200*2510	ISO 40ft Contaienr	S12R-PTA2	●	12V	49.03	E	Water
KGM1500	1650	1320	1500	1200	240	4515*2200*2510	ISO 40ft Contaienr	S12R-PTAA2	●	12V	65.37	E	Water
KGM1750	1915	1532	1750	1400	268	5470*2200*2510	ISO 40ft Contaienr	S16R-PTA	●	16V	65.37	E	Water
KGM1875	2100	1680	1875	1500	304	5470*2200*2510	ISO 40ft Contaienr	S16R-PTA2	●	16V	65.37	E	Water
KGM2050	2250	1800	2050	1640	307.3	5700*2292*2566	ISO 40ft Contaienr	S16R-PTAA2	●	16V	65.37	E	Water
KGM2250	2500	2000	2250	1800	368	5700*2292*2566	ISO 40ft Contaienr	S16R2-PTAW	●	16V	65.37	E	Water